



Sometimes your workload is  
out of hand.



Sometimes it's not.

# Lexmark **X772e**

An intuitive colour MFP for  
your demanding workgroup!

## **Big touch-screen simplicity**

The intuitive, incredibly large colour touch-screen gives you fast, user-friendly access to vivid colour output and productivity tools.

**Up to 24 ppm in colour**

**Brilliant colour  
and business versatility unit**

**The most complete of  
cost-control tools on the market!**

## **Advanced workflow solutions**

With its embedded-solutions framework, you can benefit from Lexmark's industry-leading applications without weighing down your network.

## **Top-notch security**

Includes the latest features to help you strengthen security at every level, from production and data transmission to colour-access restrictions.

**LEXMARK**<sup>TM</sup>

# Lexmark X772e

## A simple colour solution for complex businesses

Robust yet very easy-to-use, the Lexmark X772e A4 MFP enhances your documents and processes with solid performance and brilliant 4800 Colour Quality output. Better still, it integrates seamlessly into your existing IT infrastructure and arms you with all the tools you need to work more efficiently and securely than ever before!

### Enjoy greater peace of mind

Corporate information is one of your most valuable assets. To ensure all your data and documents stay safe and sound, the Lexmark X772e comes equipped with the most sought-after security features in the industry. Among others, these include SSL data transmission, job-hold expiration, hard-disk encryption, and a new 10-digit numeric pad for increased PIN-code values.

### Streamline your processes

The Lexmark X772e offers you the ideal platform to benefit from Lexmark's industry-leading enterprise workflow solutions – such as distributed capture, electronic document distribution, on-demand forms and many others. Whether embedded or server-based, these solutions help you print less, lower costs, eliminate waste and reduce transaction cycles dramatically!

#### Print Technology

Colour Laser

#### Function

Colour Copying, Colour Printing, Colour Scanning, Faxing, Colour Network Scanning

#### Print Speed (A4 mono)

Up to 24 ppm

#### Print Speed (Letter, Colour)

Up to 25 ppm

#### Print Speed (A4 colour)

Up to 24 ppm

#### Print Speed (A4 mono) Duplex

Up to 24 spm

#### Print Speed (Letter mono)

Up to 25 ppm

#### Print Speed (Letter mono) Duplex

Up to 25 spm

#### Time to First Page (Black)

as fast as < 13 seconds

#### Time to First Page (Colour)

as fast as < 15 seconds

#### Copy Speed (A4, Black)

Up to 24 cpm

#### Time to First Copy (Black)

as fast as < 13 seconds

#### Print Resolution, Black

1200 x 1200 dpi

4800 Color Quality (2400 x 600 dpi)

#### Print Resolution, Colour

1200 x 1200 dpi, 4800 Color Quality (2400 x 600 dpi)

#### Scanning Resolution

300 X 300 dpi (colour), 600 X 600 dpi (mono)

#### Processor

800 MHz

#### Memory, standard

768 MB

#### Memory network model, maximum

768 MB

#### Expandable Memory Options

No

#### Apple Macintosh Operating Systems Supported

Mac OS X, Mac OS 9.x

#### Citrix MetaFrame

Citrix, MetaFrame and MetaFrame XP are registered trademarks or trademarks of Citrix Systems, Inc. in the U.S. and other countries. Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0., Microsoft Windows Server 2003 running Terminal Server with

Citrix MetaFrame XP Presentation Server or

Citrix MetaFrame Presentation Server 3.0, Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0, Microsoft Windows Server 2003 running Terminal Server with Citrix Presentation Server 4.0, Microsoft Windows Server 2003 x64 Edition (Standard, Enterprise) running Terminal Server with Citrix Presentation Server 4.0

#### Linux Operating Systems Supported

Red Flag Linux Desktop 4.0, 5.0, Linpus Linux Desktop 9.2, 9.3, Red Hat Enterprise Linux WS 3.0, 4.0, SUSE Linux Enterprise Server 8.0, 9.0, SUSE Linux Professional 9.1, 9.2, 9.3, Debian GNU/Linux 3.0, 3.1, Linspire Linux 4.5, 5.0

#### Microsoft Windows Operating Systems Supported

2000, NT (4.00/4.00 Server), Me, XP, Server 2003, 98 2nd Edition, XP x64, Server 2003 running Terminal Server, 2000 Server running Terminal Services, Server 2003 x64 Edition, Server 2003 x64 Edition running Terminal Services

#### Novell Operating Systems Supported

Open Enterprise Server for Netware with NDS, iPrint or Novell Distributed Print Services (NDPS), NetWare® 3.2, 4.2 (bindery), NetWare 4.2, 5.x and 6.x (NDS), NetWare 5.x, 6.x with iPrint or Novell Distributed Print Services (NDPS)

#### UNIX Operating Systems Supported

Sun Solaris SPARC 7, 8, 9, 10, HP-UX 11.00, 11.11, IBM AIX 5.1, 5.2, 5.3, Sun Solaris x86 10

#### Other Operating Systems Supported

IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform, Virtually any platform supporting TCP/IP

#### Paper Handling (Standard)

250-Sheet Output Bin, 500-Sheet Drawer, 500-Sheet Tray, Duplex Unit, Second 500-Sheet Drawer, 100-Sheet Multipurpose Feeder

#### Paper Handling Optional

Banner Media Tray

#### Paper Input Capacity (Standard)

1600 pages at 80 gsm bond

#### Paper Input Capacity (Maximum)

1600 pages at 80 gsm bond

#### Paper Output Capacity (Standard)

250 pages at 80 gsm bond

#### Paper Output Capacity (Maximum)

250 pages at 80 gsm bond

#### Copy/Fax/Scan (ADF) Paper Input Capacity

Up to 50 pages at 80 gsm bond

#### Envelope Capacity

10

#### Finishing Option

No

#### Number of Paper Inputs

4

#### Number of Paper Inputs, Maximum

4

#### Media Types Supported

Card Stock, Envelopes, Glossy paper, Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide, Banner Paper

#### Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Banner

#### Standard Ports

Ethernet 10/100BaseTX (RJ-45), USB Compatible with USB 2.0 Specification, USB Direct interface on Operator Panel

#### Optional Network Ports

Lexmark N4050e 802.11g Wireless Print Server (Print Only), External MarkNet™ N7020e Gigabit Ethernet

#### Network Printing Methods

LPR/LPD, Direct IP (Port 9100), Socket (Raw TCP/IP), IPP (Internet Printing Protocol), HTTP, NDS Queue-based Printing, NDPS/NEPS (Novell Distributed Print Services, Novell Netware Enterprise Print Services), Enhanced IP (Port 9400)

#### Network Protocol Support

TCP/IP IPv4, IPX/SPX, AppleTalk™, LexLink (DLC), TCP/IP IPv6

#### Network Security

SSL Enabled Embedded Web Server, SNMPv3, TCP/IP port access control, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPSec

#### Printable Area

4.2 mm of the top, bottom, right and left edges (within)

#### Printer Languages (Standard)

PCL 5c Emulation, PCL 6 Emulation (and PostScript 3 Emulation on E250dn), Personal Printer Data Stream (PPDS), PostScript 3 Emulation, PDF 1.5, xHTML

#### Reduce / Enlarge Range

25 - 400 %

#### Scan Area, Maximum

216 x 355.6 mm

#### Modem Speed

33.6 Kbps

#### Packaged Size (mm - H x W x D)

810 x 795 x 650; 1245 x 1219 x 1016 mm

#### Size (mm - H x W x D)

1410 x 679 x 584 mm

#### Weight (kg)

97.5 kg

#### Noise Level, Idle

30 dBA

#### Noise Level, Operating

51 dBA

#### Copier Noise Level, Operating

57 dBA

#### Scanner Noise Level, Operating

55 dBA

#### Product Guarantee

One Year Onsite Repair

#### Product Certifications

Energy Star, CSA, ICES Class A, BSMI Class A, VCCI Class A, FCC Class A, UL 60950-1, IEC 60320-1, CE Class A, CB IEC 60950-1, IEC 60825-1, GS (TUV), SEMKO, UL AR, CS, TÜV Rh, C-tick mark Class A, CCC Class A

#### Duty Cycle

Up to 120,000 (one-time monthly usage)

#### Pages

#### Specified Operating Environment

Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 3048 Meters (10,000 Feet)

#### Supplies

Ships with 10K pages\* Black, Cyan, Magenta, Yellow Return Program Print Cartridges.

Aftermarket cartridges available :

15K\* Extra High Yield CMYK Return Programme Print Cartridges. Regular cartridges also available.

10K\* High Yield CMYK Return Programme

Print Cartridges. Regular cartridges also available.

6K\* CMYK Return Programme Print Cartridges. Regular cartridges also available.

\* at 5% coverage.

#### Cost saving & environmental features

Print and hold (verify print), multi-up printing, electronic document distribution and quality printing on recycled paper help reduce paper consumption - Selectable toner-saving modes help reduce the amount of toner used on a page - Return Programme cartridges and end-of-life product management help reduce landfill.



Lexmark believes that the environment is a critical component of responsible business management and clearly demonstrates it by implementing the "4R" strategy: Reduce, Recover, Reuse and Recycle. To learn more about these programmes please visit [www.lexmark.com/recycle](http://www.lexmark.com/recycle)



With our innovative solutions and services, we help you PRINT smarter, MOVE information faster and MANAGE output more efficiently across your enterprise. Ask your local Lexmark representative for more information.

Specifications are subject to change without notice. Lexmark, Lexmark with diamond design is trademark of Lexmark International, Inc. registered in the United States and/or other countries. All other trademarks are the properties of their respective owners.

[www.lexmark.co.uk](http://www.lexmark.co.uk)

**LEXMARK**